



## Easy Installation of the HitchSafe into the Receiver

1. Remove dust cover (1) by gripping cover releases (9) and pull cover out and up.
2. Set drawer dials to opening combination (factory default 0-0-0-0)
3. Remove drawer by pushing down on drawer release (2)
4. Remove both pins (5) and foam washers (6) and insert HitchSafe into your hitch receiver (3)
5. Insert HitchSafe and line up its pin holes with receiver's (3) pin holes. You may need to remove one of the foam spacers.
6. Pull out both pin retaining bars (4) to their fullest extent
7. Insert pin (5) and foam washer (6) into hole of receiver/HitchSafe. Push the sliding bar (4) in so that the bar locks pin in place by fitting into groove on the end of pin.
8. Insert combined drawer (see "Combined Drawer Instructions" on opposite side). Make sure drawer release lever (2) is up to latch and then scramble dials.
9. Place the top part of dustcover (1) so metal hooks at top fit into slots on top of HitchSafe flange. Click solidly into place bottom cover releases (9) into their corresponding slots at bottom of HitchSafe flange.

**HitchSafe™**  
[www.hitchsafe.com](http://www.hitchsafe.com)  
 800-654-1786

*Never Be Locked Out Again!*  
*Secure/Concealed Storage*